



HIGH TEMPERATURE OUTLET SERIES



HIGH VELOCITY TASK AIR OUTLET

- No Adhesives, Silicones or Felt Gasket
- Suitable for Labs, Clean Rooms, Air Showers, Spray Booths & Ovens

ADJUSTABILITY

- Lock Down Adjustment
- Directional Air Pattern Control:
70° Global Rotation Minimum
± 35° Deflection
360° Rotation

MODEL	SIZE	A	B	D	F	H	MOUNTING HOLES
HTO-03	3	1-5/8	1-3/4	3-1/8	5	2-11/16	3
HTO-04	4	2	2-9/16	4	6	3-5/16	3
HTO-05	5	2-1/2	2-5/8	5	7	4	3
HTO-06	6	3	3-1/16	6	8	4-1/2	4

- INCHES MEASURED TO THE NEAREST 1/16 INCH

STANDARD FINISHES

- #00 mill
- #10 clear anodized
- #12 anodized powder coat
- #42 gloss black powder coat
- #43 flat black powder coat
- #52 white powder coat
- #62 grey primer powder coat
(on field painting)
- #72 silver metallic powder coat
- #99 custom color / color mach
(paint chip needed)

MATERIAL

- Heavy Gauge Aluminum

NOTES

- Mounting Screws Included

ACCESSORIES

- Flex Duct Mounting Ring
- Radial Blade Damper
RBDD-D (Duct Mounted)

PROJECT :	<h2>HTO SERIES</h2> <p>HIGH TEMPERATURE OUTLET</p>	
ARCHITECT :		
ENGINEER :		
CONTRACTOR :		
SUBMITTED BY :	DATE :	FORM # : 20043S
		DRAWN BY : MH JANUARY 2018