



## HIGH TEMPERATURE OUTLET SERIES



### HIGH VELOCITY TASK AIR OUTLET

- No Adhesives, Silicones or Felt Gasket
- Suitable for Labs, Clean Rooms, Air Showers, Spray Booths & Ovens
- Up to 500° F Operating Temperature

### ADJUSTABILITY

- Lock Down Adjustment
- Directional Air Pattern Control:  
70° Global Rotation Minimum  
± 35° Deflection  
360° Rotation

MODEL	SIZE	A	B	D	F	H	MOUNTING HOLES
HTO-03	3	1-5/8	1-3/4	3-1/8	5	2-11/16	3
HTO-04	4	2	2-9/16	4	6	3-5/16	3
HTO-05	5	2-1/2	2-5/8	5	7	4	3
HTO-06	6	3	3-1/16	6	8	4-1/2	4

- INCHES MEASURED TO THE NEAREST 1/16 INCH

### STANDARD FINISHES

- #00 mill
- #10 clear anodized

### MATERIAL

- Heavy Gauge Aluminum

### NOTES

- Mounting Screws Included

### ACCESSORIES

- Flex Duct Mounting Ring

PROJECT :	<h2>HTO SERIES</h2> <p>HIGH TEMPERATURE OUTLET</p>	
ARCHITECT :		
ENGINEER :		
CONTRACTOR :	FORM # : 20043S	
SUBMITTED BY :	DATE :	DRAWN BY : MH JANUARY 2018