



High Temperature Outlet Series



High Velocity Task / Air Outlet

- No Adhesives, Silicones or Felt Gasket
- Suitable for Labs, Clean Rooms, Air Showers, Spray Booths & Ovens
- Up to 500° F Operating Temperature

Adjustability

- Lock Down Adjustment
- Directional Air Pattern Control
- 70° Global Rotation Minimum
- ±35° Deflection
- 360° Rotation

| MODEL | Size | A | B | D | F | H | Mtg Holes |
|--------|------|-------|--------|-------|---|---------|-----------|
| HTO-03 | 3 | 1-5/8 | 1-3/4 | 3-1/8 | 5 | 2-11/16 | 3 |
| HTO-04 | 4 | 2 | 2-9/16 | 4 | 6 | 3-5/16 | 3 |
| HTO-05 | 5 | 2-1/2 | 2-5/8 | 5 | 7 | 4 | 3 |
| HTO-06 | 6 | 3 | 3-1/16 | 6 | 8 | 4-1/2 | 4 |

(Inches measured to the nearest 1/16")

Standard Finishes

- #00 mill
- #10 clear anodized

Material

- Heavy Gauge Aluminum

Notes

- Mounting Screws Included

Accessories

- Flex Duct Mounting Ring

| | | |
|-----------------------|---------------|--|
| Project : | | HTO Series High Temperature Outlet |
| Architect : | | |
| Engineer : | | |
| Contractor : | | Form # : 20043S |
| Submitted By : | Date : | Drawn By : MH January 2018 |